

## 1.1x2.4m 1500 Watt LED Grow Light Full Spectrum With Daisy Chain Design

Our Product Introduction

for more products please visit us on [growled-light.com](http://growled-light.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: ANROFU
- Certification: CE ROHS FCC DLC ETL
- Model Number: HY12-1500W-2F2-240
- Minimum Order Quantity: 1
- Packaging Details: Gross Weight:22.76kg /pcs Carton Size:1165\*145\*860mm
- Delivery Time: 3-5 working days
- Payment Terms: T/T, Western Union, MoneyGram,
- Supply Ability: 1000 pcs per day

ANROFU



LAMP BEADS  
LM281B/LM301H

UL Listed  
Waterproof Drivers

Full spectrum

### Product Specification




- Power: 1500W
- Material: Aluminium
- Input Voltage: AC100-277V
- Lumen Efficiency CRI: 160LM/W >80
- PPFD (Photosynthetic Photon Flux Density) (380-780nm): 4200μmol/m²/s
- PPE (Photosynthetic Photon Efficacy): 2.8μmol/J
- Coverage: 5x8ft
- Full Spectrum: Full Spectrum White Light/423pcs+2pcs UV 395nm +48pcs 660nm+2pcs IR 730nm+15pcs 460nm
- LED Bar: 12 Strips
- Angle: 120°
- Working Temperature: -20°C~+45°C
- Application: Indoor Plants, Hydroponic Plants



|      |      |      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|------|------|
| 794  | 824  | 842  | 858  | 893  | 889  | 848  | 817  | 796  |
| 843  | 926  | 1487 | 1021 | 1010 | 1054 | 1405 | 820  | 740  |
| 846  | 901  | 846  | 830  | 1016 | 1014 | 818  | 972  | 1487 |
| 8102 | 1012 | 8178 | 8174 | 1017 | 1014 | 8178 | 1051 | 1014 |
| 8180 | 1014 | 1001 | 8101 | 1017 | 1041 | 8101 | 1046 | 1040 |
| 8108 | 1012 | 8172 | 8181 | 1016 | 1014 | 8181 | 1052 | 1011 |
| 843  | 1014 | 8405 | 8172 | 1018 | 1015 | 8148 | 876  | 1487 |
| 846  | 902  | 848  | 817  | 1011 | 903  | 140  | 927  | 842  |
| 794  | 824  | 842  | 858  | 894  | 889  | 848  | 817  | 796  |

SAMSUNG  
LM281B

### More Images



## Product Description

### DESCRIPTION

**【Daisy-Chain One Channel Dimmable】** This led grow light for indoor plant has a master dimmable controller to control the light intensity required for different plant growth stages. One channel dimmer is easy for client to dimmable the different wavelength of spectrum. The daisy-chain function allows you to connect 50-100 LED grow lamps and can be dimmed simultaneously.

**【Max 5x8ft Coverage Area Plant Lamp Full Spectrum】** 1500Watts (Full spectrum white light/423pcs+2pcs UV 395nm+48pcs 660nm+2pcs IR 730nm+15pcs 460nm) is perfect for vegetable to grow, 12 pcs LED strip light bars, it can provide evenly distributed light intensity.It can coverage for 5x8ft of high-yielding full-cycle growth.

**【Approved UL CE Certificate Power Supply and Foldable Aluminium Bracket 】** The driver of our grow lights is 1500 Watts with approved UL CE certificate and the high energy efficiency with 2.8  $\mu\text{mol/J}$ , and also has the IP54 waterproof grade for indoor plants. Our full spectrum grow lights can up to 50,000 hours to work.

**【Premium Quality for Heatsink and No Noise】** Our grow lights are made of 12 led strip aluminium bars, which has efficient heat dissipation with cooling functions. it's powerful heat dissipation ability that no need to buy more cooling devices.This led plant light has no fan, there will be no noise.

**【5 years Warranty and professional Guidance】** We provide 5 years warranty .we are gladly to give you professional guidance and friendly customer service to helps your plants grow better. If you have any questions, please contact us anytime.


660nm red lights is most useful for plant photosynthesis, promote plant flowering and fruiting, increase yield and crop quality.

730nm IR light is most useful for plant photosynthesis, promote plant flowering and fruiting, increase yield and crop quality.


### SPECIFICATION

|   |   |
|---|---|
| <b>Product Name</b>                                   | <b>1500W LED Grow Light</b>   |
| Model number  | HY12-1500W-2F2-240  |
| Power   | 1500W $\pm$ 5%  |
| Input voltage   | 110-277VAC 50/60Hz  |
| Channel   | 1 channel   |
| Dimmable  | 0-10V Dimmer  |
| LED Driver  | UL CE Driver  |
| Lumen   | 240000LM  |
| Lumen efficiency CRI                                  | 160LM/W >80   |
| PPFD (Photosynthetic Photon Flux Density) (380-780nm) | 4200 $\mu\text{mol/m}^2/\text{s}$   |
| PPE (Photosynthetic Photon Efficacy)                  | 2.8 $\mu\text{mol/J}$   |
| Full spectrum   | Full spectrum white light/423pcs+2pcs UV 395nm +48pcs 660nm+2pcs IR 730nm+15pcs 460nm             |
| Coverage  | 5x8ft   |
| Mounting height                                       | $\geq$ 6" (15.2cm) Above canopy   |
| Supplementation time                                  | Vegetative Stage: 12 - 14 hours on; Flowering Stage: 9-12 hours on; Fruiting Stage: 7-8 hours on. |
| Product size  | 2400*1100mm   |
| PF  | >0.95   |
| THD   | <15%  |
| LED Bar   | 12 strips   |
| Angle   | 120°  |
| Housing color/Material                                | Silver/Aluminium  |
| IP  | IP54 (Indoor using)   |
| Lifespan  | >50,000H  |
| Working Temperature                                   | -20°C~+45°C   |
| Operating Humidity                                    | <95%  |
| Storage Temperature                                   | -40°C~+80°C   |
| Input voltage(AC)                                     | 100 V 208 V 240 V 277 V   |
| Input current at 100%                                 | 12.5A 7.4A 6.4A 5.5A  |

Dimension(mm  $\pm$ 2mm)



**Spectrum**



**PPFD Distribution**

**30cm**

|      |      |      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|------|------|
| 825  | 832  | 891  | 924  | 934  | 894  | 883  | 843  | 796  |
| 863  | 999  | 1051 | 1082 | 1251 | 1122 | 1046 | 989  | 831  |
| 935  | 1264 | 1289 | 1292 | 1431 | 1285 | 1282 | 1255 | 936  |
| 952  | 1264 | 1283 | 1387 | 1445 | 1388 | 1284 | 1261 | 946  |
| 1008 | 1294 | 1299 | 1312 | 1450 | 1302 | 1295 | 1290 | 1007 |
| 935  | 1262 | 1281 | 1286 | 1343 | 1285 | 1283 | 1252 | 981  |
| 934  | 1151 | 1283 | 1284 | 1336 | 1282 | 1281 | 1157 | 937  |
| 827  | 994  | 1051 | 1062 | 1240 | 1126 | 1042 | 986  | 826  |
| 812  | 834  | 897  | 899  | 930  | 896  | 894  | 835  | 794  |

45cm

|     |      |      |      |      |      |      |      |     |
|-----|------|------|------|------|------|------|------|-----|
| 758 | 789  | 799  | 882  | 883  | 881  | 798  | 786  | 756 |
| 824 | 881  | 836  | 1066 | 1142 | 1062 | 934  | 879  | 826 |
| 872 | 943  | 1042 | 1121 | 1243 | 1116 | 1036 | 937  | 869 |
| 942 | 1126 | 1148 | 1187 | 1252 | 1189 | 1142 | 1124 | 941 |
| 994 | 1173 | 1187 | 1196 | 1272 | 1198 | 1184 | 1178 | 996 |
| 943 | 1126 | 1139 | 1184 | 1246 | 1185 | 1138 | 1122 | 937 |
| 868 | 937  | 1036 | 1116 | 1240 | 1113 | 1033 | 936  | 867 |
| 829 | 874  | 925  | 1063 | 1234 | 1054 | 928  | 877  | 826 |
| 752 | 768  | 799  | 834  | 885  | 837  | 792  | 761  | 751 |

60cm

|     |     |     |     |     |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 684 | 699 | 742 | 859 | 886 | 853 | 737 | 696 | 681 |
| 773 | 745 | 749 | 839 | 893 | 835 | 747 | 742 | 768 |
| 793 | 798 | 848 | 866 | 917 | 862 | 837 | 791 | 790 |
| 812 | 821 | 874 | 895 | 949 | 891 | 863 | 798 | 799 |
| 843 | 921 | 936 | 948 | 957 | 945 | 933 | 925 | 836 |
| 814 | 826 | 863 | 897 | 949 | 894 | 861 | 823 | 811 |
| 792 | 798 | 847 | 869 | 914 | 864 | 843 | 796 | 794 |
| 763 | 796 | 834 | 942 | 894 | 835 | 831 | 793 | 765 |
| 687 | 674 | 742 | 856 | 888 | 852 | 739 | 676 | 688 |

**ANROFU** Shenzhen Hanyuan Intelligent Technology Co., Ltd.



+86 15017943686



wanghaiyan@anrofu.com



growled-light.com

3 Floor No.70,Zhulong Load, Fourth Industrial Shiyuan Street Bao'An District Shenzhen City,Guangdong,China